

26 ORCHARD DRIVE, TONBRIDGE, KENT, TN10 4LG. Tel: 01732 352532

david.smith@technis.org.uk www.technis.org.uk

CERTIFICATE of RELIABILITY

FUNCTIONAL SAFETY

This is to certify that

The AWT 420 Transmitter, provided by ABB Limited, Oldends Lane, Stonehouse, GL10 3TA, Gloucestershire, UK has been assessed and is considered suitable for use in low and high demand safety functions:

As a simplex item (ie hardware fault tolerance of 0) at SIL 1 (low and high demand)

This claim is in respect of an FMEDA and some data, addressing random hardware failures and architectural constraints (ie safe failure fraction). The assessment was based on the assumptions and recommendations given in Technis Report T1062 (Issue 1.0). The product was assessed against the failure modes:

• Fail to provide an appropriate 4-20ma output

Spurious response despite no valid change

The assessment was carried out having regard to the guidance in IEC 61508 [2010] and the related body of

guidance in respect of Random Hardware Failures and Architectural Constraints [route 1H]

idance in respect of Kandom Hardware Pa	PFD	So called "dangerous" Failure Rate pa	SFF
Analogue pH Failure to provide an appropriate 4-20mA output	2.3 10 ⁻³	1.2 10-2	>87% Type B
<u>Digital pH</u> Failure to provide an appropriate 4-20mA output	2.5 10 ⁻³	1.3 10-2	>87% Type B
Conductivity Failure to provide an appropriate 4-20mA output	2.6 10 ⁻³	1.3 10-2	>87% Type B
Dissolved O ₂ Failure to provide an appropriate 4-20mA output	2.4 10 ⁻³	1.3 10-2	>87% Type B
Analogue Turbidity Failure to provide an appropriate 4-20mA output	2.3 10 ⁻³	1.2 10-2	>75% Type A
Digital Turbidity Failure to provide an appropriate 4-20mA output	2.5 10 ⁻³	1.3 10 ⁻²	>87% Type B
Digital Chlorine Failure to provide an appropriate 4-20mA output	2.4 10 ⁻³	1.2 10-2	>87% Type B
Analogue Chlorine Failure to provide an appropriate 4-20mA output	2.4 10 ⁻³	1.3 10 ⁻²	>87% Type B

The validity of this certificate requires that the product is used in accordance with any assumptions, limitations or intervals stipulated in the underpinning reliability/integrity report. The product build state continues to conform to the drawings and issues quoted in the underpinning reliability/integrity report. The product is used having regard to the instructions, limitations of use, intervals etc as outlined in the manufacturer's Safety Manual. The manufacturer maintains a credible level of Functional Safety Management in respect of (for example) design configuration control, procurement, manufacturing and defect analysis. The certificate will not apply to any product variation/modification or to the use of functions not addressed in the original study. It is recommended that the design, defect records and the company FSM procedure are reviewed, at least every 2 years, and should any changes have occurred since the original certification then the manufacture should contact Technis to request re-certification.

Signed: (Certificate No T1062-212) – 8 Sept 2022

Dr David J. Smith BSc,PhD,CEng,FIEE,FIQA,HonFSaRS,MIGasE

This certificate does not warrant fitness for any specific applications related purpose and is based on probabilistic and statistical assessment